

Check the good working order of your HVAC installations simply and economically



- Double display makes it easy-to-use
- Rugged and ergonomic casing (shock-proof protection)
- Rotating vane (Ø = 70 mm, L = 260 mm) for precise measurements up to 30 m/s

<b>Temperature</b>	
Measurement range	-20 °C to +60 °C
Resolution	0.1 °C
Accuracy	0,5 °C from 0 to 45 °C 1 °C from -20 °C to 0 and 45 °C to 60 °C
<b>Wind speed</b>	
Measurement range	0.4 to 30 m/s
Resolution	0.01 m/s
Accuracy	3 % full scale
<b>Functions</b>	MAX, MIN, MAX minus MIN, average

**Measurement units:**

- °C / °F
- m/s, km/h, knots, ft/min, mph

**Operating conditions:**

- Temperature : 0 to 50 °C
- Humidity : < 80 % HR

**Storing conditions:**

- Temperature : -20 °C to +55 °C
- Humidity : < 80 % HR

**Dimensions:**

- Device: 173 x 60.5 x 40 mm
- Sensor: 365 x 75 x 45 mm

**Total mass:** 330 g

<b>To order</b>	
C.A 822 Thermo-Anemometer	P01.1731.02

PHYSICS *Line*

C.A 822

Thermo-Anemometer

Air speed

