

## General Description:

The FHS series offer excellent stability and portability for accurate fiber optic testing. Single output port provides stable laserpower at dualwavelength. The compact unit operates in either continuous wave (CW) mode or modulated mode. A low battery indicator reminds the user of replacing the battery.



## Specifications:

	FHS -1D02	FHS -1D03
Output wavelength (nm)	1310 & 1550	850 & 1300
Emitter Type	LD	
Connector	FC/PC	
Output Stability	Short Term(15minutes):<0.1dB Long Term(5Hours or above):<0.2dB	
Central Wavelength	1310+/-20nm & 1550+/-20nm	
Spectral Width	5nm	
Output Frequency (Hz)	270,1K,2K	
Output Power	-5dBm	
Auto Power-off	Yes	
Back-light	Yes	
Operating Temperature	-10 to +50°C	
Storage Temperature	-20 to +70°C	
Power supply	2pcs*Li-ion Battery;5V AC/DC Adaptor	
Dimension (mm)	115L*65W*30H	
Net Weight	140g	

## Ordering Information:

### Standard Accessories:

FC/PC (ST/PC,SC/PC Optional) , Manual, Carrying Bag, and Battery, AC/DC charger, Test report.

Grandway Distributor:



**MCS Test Equipment Ltd**  
Unit 5-6 Station Yard,  
Llanrwst,Conwy,  
North Wales,  
LL26 0EH

Tel: 08453 62 63 65

Fax: 08453 62 36 16

Email: [sales@mcs-testequipment.co.uk](mailto:sales@mcs-testequipment.co.uk)

Web: [www.mcs-testequipment.co.uk](http://www.mcs-testequipment.co.uk)