

EUROPA PAC PLUS

Manual PAT testing at its simplest.

Quick setup

Easy test selection

Easy to use

Printer port

Large display

Full range of tests

Ideal users: ■ PAT Testers

■ Service Companies



The success of the Europa PAC Plus is down to its incredible simplicity.

It uses a large rotary switch to select the right test and gives clear indications as to how you start testing. Its large, clear digital display makes test results easy to read and there's a built-in print facility.

The Europa PAC Plus is a PAT Tester which is simple for anyone with basic training to operate. It's portable, there's no complicated menu to set up or navigate. You can test all equipment on the same day and you can also do tests to ensure that the appliance is safe after servicing. A highly efficient Tester.

Professional PATSolutions Package:

PATSolutions is a way of approaching all aspects of electrical testing. From Testers themselves to information management software. You can buy each Tester and its accessories separately or as an optional PATSolutions Package which includes everything you need to run an efficient, effective PAT testing business.

- Europa PAC Plus Tester
- Calibration certificate
- Connectors
- PATGuard support contract
- Carry case
- PAT Testing Guide
- PATGuard 2 Software

PAT TESTS

Earth Continuity

Test Currents	200mA DC, 10A AC
Display Range	0.01ohm - 19.99ohm
Pass Value	User Defined
Measurement Technique	4 Wire Measurement, Floating Earth

Insulation Resistance

Test Voltage	250V, 500V DC
Display Range	0.1Mohm - 100Mohm
Pass Value	User Defined

Protective Conductor Current

Test Voltage	230V
Display Range	0.1mA - 09.99mA
Pass Value	User Defined

Touch Current

Test Voltage	230V
Display Range	0.01mA - 3.50mA
Pass Value	User Defined

Substitute Leakage

Test Voltage	40V AC Nominal
Display Range	0.20mA - 19.99mA
Pass Value	User Defined

Load Test

Display Range	0kVA - 4.2kVA
---------------	---------------

IEC Lead Polarity

Tests Performed	Live/Neutral Continuity and Polarity
-----------------	--------------------------------------

ADDITIONAL INFORMATION

Voltage Range	207V - 253V, 45Hz - 65Hz
Weight & Dimensions	3.5kg / 31cm x 21cm x 8cm
Display Graphic	Large Format Custom LCD

ACCESSORIES

Hardware

PAT Checkbox (283A951)

Software

PATGuard Elite SQL 2 (352A950)
 PATGuard Elite 2 (352A910)
 PATGuard Pro 2 (352A920)
 PATGuard Lite 2 (352A930)
 PATGuard Work About 2 (336A910)

Training

Europa PAC Plus Training Course
 PATGuard 2 Software Training Course

Services

Service & Calibration
 JumpStart

Europa PAC Plus part no: 293A910
 Europa PAC Plus Professional PATSolutions part no: 324A930